

Vendor: IBM

Exam Code: C4090-454

Exam Name: IBM High-End Tape Technical Solutions

V7

Version: Demo

QUESTION 1

With TS1140 drives, if host software is used to compress the data before sending it to the drive, t	With	TS1140 drives	if host software is used	to compress the data before	sending it to the drive th	nen
---	------	---------------	--------------------------	-----------------------------	----------------------------	-----

- A. The drive will determine if the data should be compressed
- B. The drive data compression must be disabled to avoid performance issues
- C. The drive data compression must be disabled to avoid expansion of the data
- D. The Data Class parameter COMPACTION=YES must be set to optimize compression

Correct Answer: A

QUESTION 2

What is the maximum number of 3490 control units that can be defined in HOD for a TS7700?

- A. 4
- B. 8
- C. 16
- D. 256

Correct Answer: C

QUESTION 3

What is the maximum number of 3490 control units that can be defined in HOD for a TS7700?

- A. 16
- B. 32
- C. 64
- D. 256

Correct Answer: A

QUESTION 4

What drive types are supported in the IBM TS3300 Tape Library?

A. LTO drives only

- B. TS11x0 drives only
- C. Both LTO and DLT drives
- D. Both LTO and TS11x0 drives

Correct Answer: B

QUESTION 5

Which of the following is a point of information output from VEHSTATS?

- A. The active data distribution
- B. The percentage cache hit rate
- C. The usage of specific stacked volume cartridge
- D. The use of TS7700 resources of a batch job or subsystem

Correct Answer: B

QUESTION 6

As viewed from the front of the library, which frame can be configured as a service bay on the right side of the TS3500 High Availability Tape Library?

- A. 3584-S24 frame
- B. 3584-Lx3 frame
- C. 3584-SC1 frame
- D. 3584-HA 1 frame

Correct Answer: A

QUESTION 7

What is the minimum requirement for a TS7740-V06 to run release 2.0 microcode?

- A. 16GB memory installed
- B. at least 7 TB cache enabled
- C. TS1140 drives installed at the backend
- D. at least 200 MB/s processing increments enabled

Correct Answer: A

QUESTION 8

A customer wants to encrypt data written to tape drives. A competitor offers an encryption solution that encrypts the data before sending to the tape drives for compression. IBM wants to offer IBM TS1140 tape drives using the built-in encryption feature. Which competitive advantage does the IBM solution provide?

- A. The TS1140 offers the most secure encryption method available on the market
- B. The TS1140 encrypts and compresses data at the same time for best throughput
- C. The TS1140 encrypts data before compressing in order to obtain best performance
- D. The TS1140 compresses data before encrypting in order to obtain the best compression ratio

Correct Answer: D

QUESTION 9

To install an IBM 3592-007 with attached drives housed in a TS3500 Tape Library, which of the following is required?

- A. TS3500 frame with mountings to install the 3592-007 and its switches
- B. Customer-supplied standard rack using switches in one of the TS3500 frames
- C. IBM 3953 frame with switches installed either in 3953 frame or one of the TS3500 frames
- D. IBM 3952 frame with switches installed either in 3952 frame or one of the TS3500 frames

Correct Answer: D

QUESTION 10

What is the best location for a customer to check for any maintenance required for z/OS when installing a TS7700?

- A. Fix Central
- B. Bulk Volume Information Retrieval
- C. System Storage Interoperation Center
- D. Preventative Service Planning buckets

Correct Answer: D

QUESTION 11

Which two are valid grid adapter configurations in a TS7700? (Select two)

A. Two 1 Gb adapters

- B. One 10 Gb adapter
- C. Two I0Gbadapters
- D. Four 10 Gb adapters
- E. One 1 Gb adapters and one 10 Gb adapters

Correct Answer: AC

QUESTION 12

A customer is in the process of installing a two node TS7740 grid with a single production site. The second site used for DR is 50 km away. They want to set all logical volumes to have a size of 6 GB. What is a possible effect on the customer\\'s tape workload?

- A. It may increase the recall time for logical volumes
- B. It may increase the amount of data stored on stacked volumes
- C. It may increase the mount time for fast ready scratch volumes
- D. It may increase the amount of data stored in the tape volume cache

Correct Answer: A