Exam : **ED0-001**

Title : ericsson msc/bsc

competence exam

Version: DEMO

1. Which of the following commands is used to add a device to the route?
A. EXDRI
B. EXDAI
C. EXDRP
D. EXDRE
Answer:A
2. Which of the following is the correct command sequence for a CP Fault?
A. REPRI,REMRI,RECRI
B. REPCI,REMCI,RECCI
C. RECCI,REPCI,REMCI
D. GSTEI,NTTEI,TCTDI
Answer:B
3. Which of the following commands is used to make a copy of backup file RELFSW1 to the oldest file in
the SFR group?
A. SYTUC
B. SYNIC
C. SYSFT
D. SYFSC
Answer:C
4. A rolling database of active and previous hardware alarms can be viewed using?
A. ATR
B. ALB
C. ALV
D. ASM
Answer:B
5. Which file is used for automatic data dumps and automatic system reloads?
A. RELFSW0
B. RELFSW1
CRELFSW2
D. RELFSW100
Answer:A
6. What MOs can be tested with a command-ordered equipment test?
A. TG,TRXC,TX,RX and TS
B CF IS TF TRXC TX RX and TS

C. TG,CF,IS,TF,TRXC,RX,TX and TS
D. TG,TS,RX and TX
Answer:B
7. Which of the following commands is used to define a channel group for a cell?
A. RLDEI
B. RLDGI
C. RLDEC
D. RLDSI
Answer:B
8. Which of the following commands is used to print the process control in service performance log data?
A. PRINTPROCESS
B. ALIST
C. ISPPRINT
D. ALOGLIST
Answer:C
9. Which of the following pairs of commands is used to replace the software version for the Managed
Objects?
A. RXEST and RXPLI B.
RXMOI and RXMSC C.
RXMSC and RXPLE D.
RXMSC and RXPLI
Answer:D
10. Software Error Information can be retrieved by command?
A. PTRIP
B. SYRIP
C. SYDIP
D. SYRSP
Answer:B
11. When SAE individuals are increased or decreased, Program Store(PS) is affected?
A. True
B. False
Answer:B
12. OMS and STS measurement jobs for use by the NWS are created with?
A. SDM

B. SGW	
C. PMR	
D. SMIA	
Answer:D	
13. Which of the following commands is used to specify Routing Cases?	
A. ANRSI	
B. SUSR	
C. SUPRI	
D. None of the above	
Answer:A	
14. Which of the following commands is used to print out the TRH Event Log?	
A. RAHEP	
B. RAHHP	
C. RAHLP	
D. RAHTP	
Answer:A	
15. How many DCP2 are assigned to a GPRS and EDGE radio respectively?	
A. 2 and 6	
B. 3 and 6	
C. 3 and 4	
D. 2 and 8	
Answer:D	
16. The device type for the time slots on the Abis interface is a/an?	
A. RALT	
B. MALT	
C. RBLT	
D. RTLTT	
Answer:C	
17. SS7 is made up of a Message Transfer Part(MTP) and a number of User/Application parts.What User	
or Application part is used for signaling between BSC and MSC in the GSM network?	
A. BSSMAP	
B. MAP	
C. OMAP	
D. INAP	

Answer:A	
18. A real-time ???scoreboard??"¤ of current active hardware alarms on be viewed using?	
A. ATR	
B. ALB	
C. ALV	
D. ASM	
Answer:D	
19. Which of the following commands is used to activate an SS7 signaling link?	
A. S7RSI	
B. S7SLI C.	
S7LAI D.	
S70PI	
Answer:C	
20. Which of the following commands is used to print the CP EVENT RECORD data?	
A. DICRP	
B. DIRCP	
C. DICEP	
D. DIECP	
Answer:B	

Trying our product!

- ★ 100% Guaranteed Success
- ★ 100% Money Back Guarantee
- ★ 365 Days Free Update
- ★ Instant Download After Purchase
- ★ 24x7 Customer Support
- ★ Average 99.9% Success Rate
- ★ More than 69,000 Satisfied Customers Worldwide
- ★ Multi-Platform capabilities Windows, Mac, Android, iPhone, iPod, iPad, Kindle

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:





Guarantee & Policy | Privacy & Policy | Terms & Conditions

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © 2004-2014, All Rights Reserved.