**Exam** : MD0-205

Title : Mcdata Certified Storage

network designer exam

Version: Demo

1. Which application allows you to export a McDATA SAN Router configuration?
A. EFCM Basic
B. SANtegrity
C. SANavigator
D. EFCM
E. SANvergence Manager Answer: E
2. Which method is best used to specify which servers can access specific LUNs?
A. HBA driver configuration
B. LUN masking in the switch
C. LUN mapping in the server
D. persistent binding in the server
E. LUN masking in the storage array Answer: E
3. Which of the following is required to achieve 99.999% availability?
A. Dual rack installation
B. Separate power circuits
C. Router connectivity to DR site
D. Dual partitioned Intrepid 10000 Answer: B
4. A customer has significant power considerations. They want to purchase a switch from McDATA that uses the least power while still maintaining power supply redundancy. Which switch is the best choice for them?
A. Intrepid 10000
B. Intrepid 6140
C. Sphereon 3232

D. Sphereon 4300 E. Sphereon 4500 Answer: E 5. Which two technologies provide Fibre Channel over IP services? (Choose two.) A. SES B. iFCP C. FCIP D. iSCSI E. **FICON** F. FC-SB2 Answer: BC 6. Click the Exhibit button. Which technology is illustrated in the exhibit? Main Data Center Remote Site **Multiple SAN Fabrics** FC to IP Gateway FC to IP Gateway A. VPN B. iFCP C. FCIP D. iSCSI Answer: B

7. On the McDATA Intrepid 10000, the upper two or the lower two optical paddles in a Line Module (LIM)

A. 2 Gbps

cannot both be \_\_\_\_\_in a supported configuration.

B. 4 Gbps
C. 8 Gbps
D. 10 Gbps Answer: D
8. A customer would like to backup an application via the SAN Infrastructure. When the server offloads the backup job to a backup server which performs the backup to SAN attached tape drives, this is a common example of?
A. Server-less backup
B. Hybrid LAN backup
C. Virtual tape backup
D. Tape stripping Answer: A
9. Which three features must a switch or director have to support FICON cascading? (Choose three.)
A. port binding
B. fabric binding C.
switch binding D.
Open Trunking
E. persistent binding
F. Insistent Domain IDs Answer: BCF
10. A customer has a requirement that tape backup not interfere with application throughput. Which two options can accomplish this? (Choose two.)
A. Install an HBA for tape traffic
B. Create a separate tape SAN
C. Utilize a LAN-free backup solution
D. Increase ISL connectivity between switches Answer: AB

11. Given an environment with a mixture of 1 Gbps and 2 Gbps HBAs connecting to a 2 Gbps switch to a 2 Gbps storage array; which of the following statements is true?
A. 1 Gbps and 2 Gbps devices cannot be mixed on a 2 Gbps switch
B. 2 Gbps devices will negotiate down to 1 Gbps
C. 1 Gbps devices will negotiate up to 2 Gbps
D. Devices will communicate at both 1 and 2 Gbps Answer: D
12. Which two characteristics of a customer's infrastructure are relevant to a Storage Area Network design? (Choose two.)
A. Type of SCSI connectors
B. Number of existing storage ports C.
Number of applications per server D.
Type of fiber optic cabling installed
E. Distance between client workstation and server Answer: BD
13. For security purposes, what is used to prevent Fibre Channel frames from being stored after a switch is powered off or has failed?
A. FMS
B. OSMS
C. Full Volatility
D. Open Trunking Answer: C
14. When adding a switch to an existing SAN, which two statements are true? (Choose two.)
A. Domain IDs must be unique.
B. Port counts should be the same on all switches.
C. RA_TOV should be consistent across the switches.

D. IP addresses and masks for management must be defined.
E. Zoning of the new switch must be done prior to E_port connections.  Answer: AC
15. Which three configuration changes require the McDATA Eclipse 1620 to be reset? (Choose three.)
A. SNMP traps
B. zoning changes
C. firmware upgrade
D. SNS configuration
E. management parameters Answer: CDE
16. You are planning a Disaster Recovery (DR) solution over iFCP using Eclipse SAN Routers. What should be equal in both connected fabrics?
A. Zone ID B.
Fabric ID C.
Domain ID D.
IP address
E. storage array port number Answer: A
17. What is the McDATA supported limit of the number of switches in a single fabric?
A. 12
B. 16
C. 24
D. 31
E. 239 Answer: C
18. Which configuration offers a customer the highest availability (99.999%)?

A. dual switch, dual fabric connectivity B. dual switch, single fabric connectity C. dual director, dual fabric connectivity D. single director, single fabric connectivity E. single partitioned director, dual fabric connectivity Answer: C 19. A customer has 1u of rack space available and has a requirement for 99.99% availability. What products would you recommend if they plan on implementing a SAN? A. Single Intrepid 6140 Director B. Two Sphereon 4700 Switches C. Two Sphereon 4400 Switches D. Two Eclipse 2640 SAN Routers Answer: C 20. Which function would you recommend to automatically block E\_Ports when error thresholds are reached? A. ISL Binding B. Port Fencing C. Open Trunking D. Threshold Alerts

Answer: B

## **Trying our product!**

- ★ 100% Guaranteed Success
- ★ 100% Money Back Guarantee
- ★ 365 Days Free Update
- ★ Instant Download After Purchase
- ★ 24x7 Customer Support
- ★ Average 99.9% Success Rate
- ★ More than 69,000 Satisfied Customers Worldwide
- ★ Multi-Platform capabilities Windows, Mac, Android, iPhone, iPod, iPad, Kindle

## **Need Help**

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:





## Guarantee & Policy | Privacy & Policy | Terms & Conditions

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © 2004-2014, All Rights Reserved.