

Exam : **HT0-102**

Title : HTI+ Systems Infrastructure
and Integration

Version : DEMO

1. Which of the following serial protocols allows the daisy chaining of devices?

- A. Fire Wire
- B. RS-232
- C. RS-422
- D. RS-485

Answer: D

2. Which of the following is a requirement of a home automation system that allows the system to be set up for out of band remote maintenance from an off-site location?

- A. Dial-in modem
- B. Local terminal C.
Infrared remote
- D. Wireless access point

Answer: A

3. Which of the following is a support that is mounted to the backboard and used to manage cables?

- A. Conduit
- B. 66 block
- C. D-ring
- D. Cable tray

Answer: C

4. A technician is programming the locations for 802.11 devices used in home automation. Which of the following describes the Layer 2 address of the OSI model?

- A. IP address
- B. MAC address
- C. X10 address
- D. 802.11 address

Answer: B

5. The design of a system requires a wall-mounted control device that works with a RS-485 based control processor. Control needs to be available at 16 locations. The interface should allow the technician to customize the menu options with icons and text associated with each of the push buttons. Which of the following meets the design criteria?

- A. Web pad
- B. LCD keypad
- C. If remove control
- D. Touch screen controller

Answer: B

6. One of the devices used to control a multimedia center uses serial communications to receive instructions from the system controller. The device needs to be tested off-line, and it has been disconnected from the system controller. A notebook computer equipped with a serial port is available for testing. Which of the following cables will complete the connection?

- A. Coaxial
- B. Patch
- C. Telephone D.
- Null-modem

Answer: D

7. An integrated home automation system is being designed to use a personal computer equipped with a single IEEE 1394 port. What is the total number of devices that additional ports are needed?

- A. 23
- B. 43
- C. 63
- D. 83

Answer: C

8. Which of the following methods offer protection from attenuation in larger installations using an X10 protocol to control devices?

- A. IR repeater
- B. Signal bridge
- C. RS-232 to RS-485 converter
- D. 75 ohm to 100 ohm converter

Answer: B

9. The IEEE 1394 interface is commonly referred to as:

- A. SCSI
- B. FireWire™
- C. Fast Ethernet
- D. Gigabit Ethernet

Answer: B

10. Which of the following standards has the greatest maximum distance from the central office of the telephone company to the home?

- A. ADSL
- B. SDSL

- C. IDSL
- D. G.SHDSL

Answer: C

11. Which of the following systems utilizes the electrical cabling as a control media throughout the house?

- A. PLC
- B. HomeRF
- C. HomePNA
- D. Broadband coaxial

Answer: A

12. Which of the following does NOT need to be documented for a control system?

- A. System diagram
- B. Equipment list
- C. Configuration of equipment
- D. Equipment specifications

Answer: D

13. In a wireless security system, the controller should monitor each transmitter for:

- A. high interference
- B. low radiation level
- C. high humidity
- D. low battery

Answer: D

14. Which of the following devices is required by the Federal Communications Commission (FCC) for registered alarm connections in which alarm panels are connected to a telephone line?

- A. RJ-11
- B. RJ-21
- C. RJ-31X
- D. RJ-45

Answer: C

15. Which of the following terms describes a point or group of points in an alarm system?

- A. Zone
- B. Area
- C. Perimeter
- D. Demarcation

Answer: A

16. Which of the following tools is used to fasten a connector to a cable end?

- A. Crimper
- B. Wire strippers
- C. Lineman's pliers
- D. Punch-down tool

Answer: A

17. Which of the following authorities establish the National Electrical Code (NEC) as legal regulations?

- A. Local fire marshal
- B. Local governments
- C. Building contractors
- D. National Fire Protection Association (NFPA)

Answer: B

18. Which of the following ANSI/TIA/EIA standards most directly concerns residential low-voltage telecommunication cabling?

- A. 568-B
- B. 570
- C. 570-A
- D. 606

Answer: C

19. A programmable HVAC thermostat can be accessed remotely to:

- A. warn of a high heating bill
- B. light up the thermostat in dark hallways
- C. power the HVAC upon the loss of AC power
- D. allow the panel to control the temperature settings of the thermostat

Answer: D

20. Which of the following devices will prevent the loss of functionality during a sudden alternating current (AC) power outage?

- A. Dedicated circuit
- B. Surge protector
- C. Transfer switch
- D. Uninterruptible Power Supply (UPS)

Answer: D

Trying our product !

- ★ **100%** Guaranteed Success
- ★ **100%** Money Back Guarantee
- ★ **365 Days** Free Update
- ★ **Instant Download** After Purchase
- ★ **24x7** Customer Support
- ★ Average **99.9%** Success Rate
- ★ More than **69,000** Satisfied Customers Worldwide
- ★ Multi-Platform capabilities - **Windows, Mac, Android, iPhone, iPod, iPad, Kindle**

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 One Year Free Update <p>Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 Money Back Guarantee <p>To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 Security & Privacy <p>We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Guarantee & Policy | Privacy & Policy | Terms & Conditions

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © 2004-2014, All Rights Reserved.