Vendor: Salesforce

Exam Code:ANC-301

Exam Name: Working with Data and Dashboards in Einstein Analytics

Version: Demo

QUESTION 1

Which three statements are true regarding sharing inheritance? Choose 3 answers

A. If a user can see more than 3,000 records on the object in Salesforce, but the user does not have the "View All Data" permission, sharing inheritance is not used. The backup security predicate takes effect. This limitation does not apply to the Opportunity object.

B. Sharing inheritance supports Account, Campaign, Case, Contact, Opportunity, Lead, Order, User, and custom objects. If you use other objects, such as Idea or Site, you must use security predicates for those objects.

C. A dataset using sharing must also have a security predicate defined.

D. Sharing inheritance supports a foreign key for enforcing security.

E. When sharing inheritance is enabled, security predicates are ignored.

Correct Answer: ABC

https://help.salesforce.com/articleView?id=bi_security_datasets_sharing_about.htmandtype=5

QUESTION 2

Yasmine wants to create a lens with the Seed Bank Orders dataset, but she currently doesn\\'t see any rows in the dataset. Since Yasmine is Hadiqa\\'s manager, Yasmine asks Hadiqa if she\\'s experiencing the same problem, but Hadiqa replies that she can see all the rows. Why is this happening?

A. The dataset\\'s security predicate was set up incorrectly.

B. Yasmine doesn\\'t have the Manager app role.

C. Yasmine wasn\\'t assigned a permission set.

D. Yasmine doesn\\'t have the Create and Edit Analytics Dashboards permission.

Correct Answer: A

QUESTION 3

The Universal Containers company used Einstein Analytics to create two datasets:

Dataset A: contains a list of activities with an "activityID" dimension and a "userID" dimension Dataset B: contains a list of users with a "userID" dimension

The team wants to delete from Dataset A all activities related to users in Dataset B.

How can an Einstein Consultant help them achieve this?

A. Use the dataflow transformation "delete" and set "userID" as the deletion ID.

B. Use a combination of dataflow transformations: "augment" and "filter."

C. Use an external ETL tool to extract both datasets and delete records.

D. Use the recipe operation "delete" and set "userID" as the deletion ID.

Correct Answer: B

QUESTION 4

What kind of insight is "What Is The Difference"?

A. Descriptive

B. Diagnostic

C. Predictive

D. Prescriptive

E. Selective

Correct Answer: B

https://trailhead.salesforce.com/content/learn/modules/understand_einstein_discovery_stories/understandwhat-is-the-difference-insights

---

QUESTION 5

What is the test called that helps to identify categories that exhibit a pattern outside the overall average?

A. Null hypothesis test

B. Significance level test

C. Critical region test

D. Chi-square test

E. T-test

Correct Answer: E

QUESTION 6

The Universal Containers Einstein Analytics team built a dashboard with two widgets:

1.

List widget associated to the step "Type_2" and grouped by the dimension "Type" (multi-selection)

2.

Pie chart widget associated to the step "Step_pie_3" and grouped by the dimension "Type" The team wants to use bindings so any selection in the List widget will filter the Pie chart. Additional notes:

*

The steps use different datasets.

*

Users should be able to choose more than one Type (multi-selection). What is the right syntax for the binding?

A.

Option A

B.

Option B

C.

Option C

D.

Option D

Correct Answer: C

A.

```
"filter": [
            [
                "Type",
                "{{column(Type_2.selection, [\"Type"]).asString()}}"
            ]
        ]
```

B.

```
        ]
"filter": [
            [
                "Type",
                "{{cell(Type_2.selection, 0, \"Type\").asString()}}"
            ]
        ]
```

C.

```
"filter": [
            [
                "Type",
                "{{column(Type_2.selection, [\"Type"]).asObject()}}"
            ]
        ]
```

D.

```
"filter": [
            [
                "Type",
                "{{cell(Type_2.selection, 0, \"Type\").asObject()}}"
            ]
        ]
```

QUESTION 7

Default # rows in compare table.

A. 1500

B. 1000

C. 3000

D. 2000

Correct Answer: D

QUESTION 8

A consultant built a very useful Einstein Analytics app for Sales Operations, and they want to share its contents with the rest of Global Sales. However, they do not want to add everyone in Sales to their app. The consultant recommends extending the Sales Operations app and distributing it as an Einstein

```
{
    "folderSource" : { "id" : "Sales Operations ID"}
}
```

Analytics template app, but needs to locate specific information to get started.

Given the code statement above, which endpoint should it be posted to?

A. /services/data/v##.#/wave/apps

B. /services/data/v##.#/analytics/wizard

C. /services/data/v##.#/analytics/projects

D. /services/data/v##.#/wave/templates

Correct Answer: D

https://developer.salesforce.com/docs/atlas.en-us.bi_dev_guide_rest.meta/bi_dev_guide_rest/bi_resources_templates.htm

---

QUESTION 9

Default rows in values table

A. 100

B. 200

C. 50

D. 75

Correct Answer: A

QUESTION 10

How many concurrent stories per org are allowed?

A. 5

B. 4

C. 2

D. 1

Correct Answer: C

QUESTION 11

You can configure access to data at all of the following levels, except:

A. Organization

B. Records

C. Page Layouts

D. Objects

Correct Answer: C

QUESTION 12

A consultant built a very useful Einstein Analytics app for Sales Operations and they want to share its contents with the rest of Global Sales. However, they do not want to add everyone in Sales to their app. The consultant recommends extending the Sales Operations app and distributing it as an Einstein Analytics template app, but needs to locate specific information to get started.

What is the REST API URL where the consultant can find current template apps?

A. /services/data/v##.#/wave/apps

B. /services/data/v##.#/analytics/wizard

C. /services/data/v##.#/wave/templates

D. /services/data/v##.#/analytics/projects

Correct Answer: B