

Vendor:F5

Exam Code:F50-531

Exam Name: BIG-IP v10.x LTM Essentials V10.x

Version:Demo

QUESTION 1

A site is load balancing to a pool of web servers. Which statement is true concerning BIG-IP\\'s ability to verify whether the web servers are functioning properly or not?

- A. Web server monitors can test the content of any page on the server.
- B. Web server monitors always verify the contents of the index.html page.
- C. Web server monitors can test whether the server\\'s address is reachable, but cannot test a page\\'s content.
- D. Web server monitors can test the content of static web pages, but cannot test pages that would require the web server to dynamically build content.

Correct Answer: A

QUESTION 2

A virtual server is listening at 10.10.1.100:any and has the following iRule associated with it: when CLIENT_ACCEPTED { if {[TCP::local_port] equals 21 } { pool ftppool } elseif {[TCP::local_port] equals 23 } { pool telnetpool } If a user connects to 10.10.1.100 and port 22, which pool will receive the request?

- A. ftppool
- B. telnetpool
- C. None. The request will be dropped.
- D. Unknown. The pool cannot be determined from the information provided.

Correct Answer: D

QUESTION 3

Where is persistence mirroring configured?

- A. It is always enabled.
- B. It is part of a pool definition.
- C. It is part of a profile definition.
- D. It is part of a virtual server definition.

Correct Answer: C

QUESTION 4

How is MAC masquerading configured?

- A. Specify the desired MAC address for each VLAN for which you want this feature enabled.
- B. Specify the desired MAC address for each self-IP address for which you want this feature enabled.
- C. Specify the desired MAC address for each VLAN on the active system and synchronize the systems.
- D. Specify the desired MAC address for each floating self-IP address for which you want this feature enabled.

Correct Answer: A

QUESTION 5

When using the setup utility to configure a redundant pair, you are asked to provide a "Failover Peer IP". Which address is this?

- A. an address of the other system in its management network
- B. an address of the other system in a redundant pair configuration
- C. an address on the current system used to listen for fail-over messages from the partner BIG-IP
- D. an address on the current system used to initiate mirroring and network fail-over heartbeat messages

Correct Answer: B

QUESTION 6

Which two statements describe differences between the active and standby systems? (Choose two.)

- A. Monitors are performed only by the active system.
- B. Fail-over triggers only cause changes on the active system.
- C. Virtual server addresses are hosted only by the active system.
- D. Configuration changes can only be made on the active system.
- E. Floating self-IP addresses are hosted only by the active system.

Correct Answer: CE

QUESTION 7

Which statement is true concerning SSL termination?

- A. A virtual server that has both ClientSSL and ServerSSL profiles can still support cookie persistence.
- B. Decrypting traffic at the BIG-IP allows the use of iRules for traffic management, but increases the load on the pool member.
- C. When any virtual server uses a ClientSSL profile, all SSL traffic sent to the BIG-IP is decrypted before it is forwarded

to servers.

D. If a virtual server has both a ClientSSL and ServerSSL profile, the pool members have less SSL processing than if the virtual server had only a ClientSSL profile

Correct Answer: A

QUESTION 8

A virtual server is defined per the charts. The last five client connections were to members C, D, A, B, B. Given the conditions shown in the above graphic, if a client with IP address 205.12.45.52 opens a connection to the virtual server, which member will be used for the connection?

Available

Available

22

18

VS_Web_Pool Settings			Web_Pool Parameters		
Destination	: 10.10.20	0.100:80	Load Balancing	Least Connections	
Profiles:	тср, нттр		Priority Group Activation:	Less Than 2	
iRules:	None		Monitor:	Custom_HTTP	
Default Poo	i: Web_P	loo			
Persistence	None				
	Web_Poo	Member	Statistics and	Settings	
Member	Member Ratio	Member Priority	Outstanding Requests	Current Connections	Status
A: 172.16.20.1:80	3	5	4	56	Unavailable
B: 172.16.20.2:80	3	4	4	42	Available
C: 172.16.20.3:80	3	5	4	54	Unavailable

A. 172.16.20.1:80

D: 172.16.20.4:80

E: 172.16.20.5:80

B. 172.16.20.2:80

C. 172.16.20.3:80

D. 172.16.20.4:80

E. 172.16.20.5:80

Correct Answer: D

QUESTION 9

A site needs to terminate client HTTPS traffic at the BIG-IP and forward that traffic unencrypted. Which two are profile types that must be associated with such a virtual server? (Choose two.)

A. TCP

- B. HTTP
- C. HTTPS
- D. ClientSSL
- E. ServerSSL

Correct Answer: AD

QUESTION 10

When initially configuring the BIG-IP system using the config utility, which two parameters can be set? (Choose two.)

- A. the netmask of the SCCP
- B. the IP address of the SCCP
- C. the port lockdown settings for the SCCP
- D. the netmask of the host via the management port
- E. the IP address of the host via the management port
- F. the port lockdown settings for the host via the management port

Correct Answer: DE

QUESTION 11

Which process or system can be monitored by the BIG-IP system and used as a fail-over trigger in a redundant pair configuration?

- A. bandwidth utilization
- B. duplicate IP address
- C. CPU utilization percentage
- D. VLAN communication ability

Correct Answer: D

QUESTION 12

Which event is always triggered when a client initially connects to a virtual server configured with an HTTP profile?

- A. HTTP_DATA
- B. CLIENT_DATA

C. HTTP_REQUEST

D. CLIENT_ACCEPTED

Correct Answer: D