100% Money Back Guarantee

Vendor:HP

Exam Code:HP2-Z33

Exam Name:HP Unified Wired-Wireless Networks and BYOD

Version: Demo

QUESTION 1

How can a network administrator set up User Manager (UAM) redundancy?

A. By installing a UAM server with two wireless controllers

B. By setting an Active and a Standby server sharing a common IP address

C. By setting an Active and Standby server sharing common storage

D. By installing two servers in a cluster where each is defined with a separate IP address and a shared virtual IP

Correct Answer: D

QUESTION 2

A customer is planning to deploy HP MSM466-R access points in an extreme cold environment to interconnect to the Unified Wired-WLAN Module in the HP switch. Which requirement is needed to accomplish this?

A. NEMA 4X enclosures should be used to house the access points.

B. Switch ports must support PoE.

C. PoE redundancy must be enabled on the interface.

D. Access Point must deploy internal antennas.

Correct Answer: B

QUESTION 3

In 802.1XEAP-TLS, how can a network administrator control network access of corporate users?

A. by selecting which user groups are entitled to deploy a certificate on their endpoints

B. by selecting which endpoints are entitled to install a certificate

C. by defining corporate users as guests

D. by disabling or deleting the user\\'s endpoint in User Access Manager

Correct Answer: B

QUESTION 4

The Wireless Intrusion Prevention System (WIPS) determines that a client has exceeded the maximum number of authentication requests that a client should make in the allowed period. What does the WIPS system do?

A. adds the client\\'s MAC address to the static blacklist on the access controller

B. adds the client\\'s MAC address to the static blacklist on the access point

C. adds the client\\'s MAC address to the dynamic blacklist for the access point

D. removes the client\\'s MAC address from the whitelist on the access controller

Correct Answer: C

QUESTION 5

A corporate user accesses a corporate network on SSID CORPORATE. The user endpoint is set up for 802.1X in PEAP-MSCHAPV2: HP BYOD is implemented.

Wireless is set up on an HP Unified Wired-Wireless Controller

Accounts have been synchronized with an Active Directory Domain controller.

A. Setup of RADIUS on the Wireless controller and User Access Manager. Certificate server installation. BYOD Portal setup

B. Setup of 802.1X Authentication on the wireless controller Installation of certificates in User Access Manager (UAM) Setup of RADIUS on the wireless controller and UAM

C. Setup of 802 1X Authentication on the wireless controller Setup of RADIUS on the wireless controller and User Access Manager Fingerprinting with the DHCP agent

D. Setup of 802 IX Authentication on the wireless controller Setup RADIUS on the wireless controller and User Access Manager Fingerprinting with the HTTP agent

Correct Answer: A

QUESTION 6

When does DHCP fingerprinting of endpoints occur within an HP BYOD solution?

A. when User Access Manager validates the user account

B. when endpoints access the BYOD registration page

C. when endpoints obtain an IP address

D. when endpoints are authenticated

Correct Answer: C

QUESTION 7

Refer to the exhibit.



A company wants to connect a mid-size branch office to their corporate location. An HP 10500/7500 Unified Wired-Wireless module is deployed at the corporate location. A maximum of six HP MSM access points will be deployed at the branch location.

Which HP device meets these customer requirements and is the most cost effective solution for the branch location?

A. HP 830

B. HP 870

C. HP 2920

D. HP 7500

Correct Answer: A

QUESTION 8

A network administrator wants to set a DNS proxy that forwards DNS traffic to a DNS Server on 10.1.1.1.

Which HP Comware command set, executed in system-view mode, is required to set this?

A. dns resolve dns proxy dns server 10.1.1.1

B. dns resolve dns proxy enable dns server 10.1.1.1

C. dns proxy resolve dns server 10.1.1.1

D. dns proxy enable dns server 10.1.1.1

Correct Answer: B

QUESTION 9

Which command allows an administrator to access the HP 830 switch CLI from the controller?

A. oap management-ip 192.168.0.101 module 1

B. oap connect slot 0

C. oap management-ip 192.168.0.101 slot 1

D. oap connect module 0

Correct Answer: B

QUESTION 10

An organization\\'s security policy mandates the use of 802.1X port based authentication. The organization\\'s security policy also mandates that before an employee\\'s personal device can connect to the wireless network, it must download anti-virus, security patch, and other essential software. What should be configured on the access point to support these requirements?

A. EAP-TLS

B. dynamic WEP

C. portal authentication

D. 802.1X guest VLAN

Correct Answer: D

QUESTION 11

What is an attribute of an autonomous AP?

A. managed through a Web browser or a command line interface

B. supported on the HP 425 AP

C. must be powered by a PoE switch

D. supports layer 2 and layer 3 roaming

Correct Answer: A

QUESTION 12

What is the purpose of Transparent MAC authentication?

A. to allow endpoints associated with a valid account to register on the BYOD page

B. to allow endpoints associated with the Default BYOD user to authenticate transparently

C. to allow endpoints associated with a valid account to authenticate transparently

D. to allow endpoints associated with a valid guest account to register on the BYOD page

Correct Answer: D