Exam : PD0-001

Title : CompTIA PDI+ Beta Exam

Version : DEMO

1.The type of data sent to the laser printer is called:A.PCL5 printer data.B.raster data.C.a bitonal image file.D.Post Script.Answer:B

2.Which of the following would be the MOST likely cause of gray background on the entire surface of a copied page?A.Improperly stored paperB.Deteriorated developer

- C.High humidity level
- D.Low toner supply
- Answer:B
- 3. Which of the following is a function of a developer bias?
- A.Decreases toner consumption
- B.Dissipates the electrical charge on the photoconductor
- C.Applies toner to the latent image
- D.Eliminates ozone emissions
- Answer:C
- 4.Which of the following is a definition of firmware?A.The amount of data contained on a PCBB.Support structure for a PCBC.Software resident on a PCBD.The variable data written to a PCBAnswer:C

5.On a system using a negative photoconductor charge, how does the toner become attracted to the latent image?

- A.By the voltage difference between the two
- B.By discharging the latent Image area to "Ground"
- C.By reducing the toner charge
- D.By the temperature difference between the two
- Answer:A

6.In a developing unit, the purpose of the developer roller is to:

A.create a static charge on the toner/developer.

B.apply charges to the toner to make it adhere to the photoconductor.

C.create the magnetic brush that holds the toner/developer.

D.apply charges to the photoconductor.

Answer:C

7. Which of the following is required in order for the primary charging process to fully charge the surface of the photoconductor?

A.The developing spacer rollers must be in contact with the photoconductor.

B.The charging corona/roller must have continuity to device ground.

C.The photoconductor must have continuity with device ground.

D.The photoconductor must be in contact with the cleaning blade.

Answer:C

8.Media weights are described in terms of:

- A.grams per square meter.
- B.pounds per linear foot.
- C.pounds per square meter.
- D.grams per square foot.

Answer:A

9.A customer has been having jamming issues and also notices the media is curled excessively. Which of the following is the potential issue?

- A.Contaminated registration roller
- B.Ozone filter needs to be replaced
- C.Using recycled media
- D.Defective toner cartridge
- Answer:C

10.During the laser printing process, how does the laser form the latent image on the photoconductor?A.Heats the surfaceB.Magnetizes the surfaceC.Charges the surfaceD.Discharges the surfaceAnswer:D

11. Which of the following processes involves discharging the photoconductor in order to create the latent image?

- A.Cleaning B.Writing C.Charging D.Development
- Answer:B

12. Which of the following processes occurs inside the dual component developer unit?

- A.Fusing of the developer
- B.Stirring of the developer
- C.Cleaning of the developer
- D.Exposing of the developer

Answer:B

13. When scanning a document on a flatbed scanner, the sub scan is determined by the:

A.darkness of the exposure setting.

B.movement of the lamp/mirror assembly across the original.

C.polygon mirror movement.

D.compression setting.

Answer:B

14. When scanning a document on a device equipped with an ADF, the main scan is determined by the: A.movement of the original.

B.CIS unit.

C.speed of the ADF.

D.compression setting.

Answer:B

15. How many mirrors can be found in MOST scanner units that contain a CCD?

A.One

B.2

C.3

D.4

Answer:C

16.Which of the following describes the purpose of the CCD?

A.To properly set the bias of the exposure lamp.

B.To properly set the bias voltages on the photoconductor.

C.To convert the scanned original image into an analog data stream.

D.To convert the scanned original image into a digital data stream.

Answer:C

17. Which of the following is the purpose of the cover that is used to conceal the lens and CCD in the flatbed scanner?

A.To reduce wear and tear on the components.

B.To allow the components to reach operating temperature faster.

C.To block stray light from altering the scanned image.

D.To reduce paper dust contamination.

Answer:C

18. Which of the following is used for reducing output from an MFP evenly in feed and crosswise directions?

A.Change the speed of the photoconductor

B.Moving the scanner optic mirror closer to the reduction lens

C.Moving the scanner optic mirror away from the reduction lens

D.Image processor circuitry

Answer:D

19.Which of the following is the MOST likely cause of light images when scanning?A.Dirty mirrorsB.Wrong scanner driverC.No output from the CCDD.Cracked lensAnswer:A

20.A user reports that they are seeing portions of the image duplicated on the document that was just printed. Which of the following is the MOST likely cause? A.Laser unit B.Transfer section C.Fuser unit D.Developer unit Answer:C

Trying our product !

- ★ 100% Guaranteed Success
- ★ 100% Money Back Guarantee
- ★ 365 Days Free Update
- ★ Instant Download After Purchase
- ★ 24x7 Customer Support
- ★ Average 99.9% Success Rate
- ★ More than 69,000 Satisfied Customers Worldwide
- ★ Multi-Platform capabilities Windows, Mac, Android, iPhone, iPod, iPad, Kindle

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





One Year Free Update Free update is available within One ter your purchase. After One ar, you will get 50% discounts for ng. And we are proud to ast a 24/7 efficient Customer t system via Emai

Money Back Guarantee To ensure that you are spending on

quality products, we provide 100% money back guarantee for 30 days from the date of purchase

Security & Privacy

We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & pea of mind.

Guarantee & Policy | Privacy & Policy | Terms & Conditions

100%

Any charges made through this site will appear as Global Simulators Limited. All trademarks are the property of their respective owners.

Copyright © 2004-2014, All Rights Reserved.